

Amendments to the Claims

This listing of claims will replace all prior versions, and listings, of claims in the application:

Listing of Claims:

1. (currently amended) A nuclear fuel assembly comprising:

A parallel array of elongated nuclear fuel elements supported between a lower nozzle and an upper nozzle and having an axial length along the elongated dimension of the nuclear fuel elements with a mid third region along the axial length;

A plurality of substantially evenly spaced main support grids arranged in tandem along the axial length of the fuel elements, between the upper nozzle and the lower nozzles, at least partially enclosing an axial portion of the circumference of each fuel rod within a support cell of the main support grids to maintain a lateral spacing between fuel elements; and

At least one auxiliary grid positioned around the fuel elements in tandem with the main support grids at an elevation in the mid third region, the auxiliary grid comprising a plurality of support cells with one support cell for each fuel element, wherein the auxiliary grid is supported between two main support grids without any other auxiliary grids between the auxiliary grid and the adjacent main support grid and wherein the main support grids have a first fuel rod support assembly and the auxiliary grid has a second fuel rod support assembly and the first and second fuel rod support assemblies are of a different design; and

wherein the auxiliary grid support cells have walls that respectively at least partially enclose a portion of the circumference of the fuel rods along a portion of their axial length and the second fuel rod support assembly is located on the walls of the auxiliary grid support cells and comprise a second set of dimples and/or springs that contact and support the fuel elements and the main support grids' cells have walls that respectively at least partially enclose a portion of the circumference of the fuel rods along a portion of their axial length and the first fuel rod support assembly is located on the walls of the main support grids' cells and comprise a first set of dimples and/or springs that contact and support the fuel elements, wherein the second set of dimples and/or springs on the auxiliary support cells have a larger contact area with the fuel elements than the first set of dimples and/or springs on the walls of the main support grid cells.

2. (original) The fuel assembly of Claim 1 wherein the auxiliary grid is supported substantially midway between two main support grids.
3. (currently amended) The fuel assembly of Claim ~~1~~2 including a plurality of auxiliary grids positioned between some, but not all of the main support grids.
4. (original) The fuel assembly of Claim 3 wherein adjacent ones of the plurality of auxiliary grids share one main support grid between them.
5. (original) The fuel assembly of Claim 3 wherein the auxiliary grids are positioned along a mid span of the fuel elements within the mid third region.
6. (canceled)
7. (currently amended) The fuel assembly of Claim 1 ~~wherein the auxiliary grid support cells have walls that respectively at least partially enclose a portion of the circumference of the fuel rods along a portion of their axial length and the main support grids' cells have walls that respectively at least partially enclose a portion of the circumference of the fuel rods along a portion of their axial length,~~ wherein the axial length of the walls of the auxiliary grid support cells is shorter than the corresponding walls of the main support grid cells.
8. (canceled)
9. (previously presented) The fuel assembly of Claim 1 wherein the dimples and/or springs on the walls of the respective auxiliary grid support cells are coplanar.
10. (previously presented) The fuel assembly of Claim 1 wherein at least some of the main support grids have mixing vanes and at least some of the auxiliary grids do not have mixing vanes.
11. (withdrawn) The fuel assembly of Claim 10 wherein at least some of the main support grids have mixing vanes and the auxiliary grids do not have mixing vanes.

12. (withdrawn) The fuel assembly of Claim 10 wherein the main support grids have mixing vanes and the auxiliary grids do not have mixing vanes.

13. (canceled)

14. (original) The fuel assembly of Claim 1 wherein the auxiliary grid has an outer strap that extends around its circumference and includes upwardly extending guide tabs that are inwardly directed at an angle of less than 90 degrees with the strap in the direction of the adjacent fuel element, to prevent hang-up with adjacent fuel assemblies during removal or insertion into a reactor core.

15. (new) A nuclear fuel assembly comprising:

A parallel array of elongated nuclear fuel elements supported between a lower nozzle and an upper nozzle and having an axial length along the elongated dimension of the nuclear fuel elements with a mid third region along the axial length;

A plurality of substantially evenly spaced main support grids arranged in tandem along the axial length of the fuel elements, between the upper nozzle and the lower nozzle, at least partially enclosing an axial portion of the circumference of each fuel rod within a support cell of the main support grids to maintain a lateral spacing between fuel elements; and

At least one auxiliary grid positioned around the fuel elements in tandem with the main support grids at an elevation in the mid third region, the auxiliary grid comprising a plurality of support cells with one support cell for each fuel element, wherein the main support grids have a first fuel rod support assembly and the auxiliary grid has a second fuel rod support assembly and the first and second fuel rod support assemblies are of a different design; and

wherein the auxiliary grid support cells have walls that respectively at least partially enclose a portion of the circumference of the fuel rods along a portion of their axial length and the second fuel rod support assembly is located on the walls of the auxiliary grid support cells and comprise a second set of dimples and/or springs that contact and support the fuel elements and the main support grids' cells have walls that respectively at least partially enclose a portion of the circumference of the fuel rods along a portion of their axial length

and the first fuel rod support assembly is located on the walls of the main support grids' cells and comprise a first set of dimples and/or springs that contact and support the fuel elements, wherein the second set of dimples and/or springs on the auxiliary support cells have a larger contact area with the fuel elements than the first set of dimples and/or springs on the walls of the main support grid cells and the full extent of the axial length of the walls of the auxiliary grid support cells is shorter than the corresponding walls of the main support grid cells.